

## EMAB03



### General

Style Number	EMAB03
Part Number	EMAB03
Availability	Usually in stock
U Height	26 [Minimum U rack]
MIB	available for download

### Physical

Dimensions (H x W x D, mm)	52x53x1154
Mounting Style	Button mounting on rear and sides, variable mounting bracket included
Form factor	0U

### Input

Max kW	2
Plug	(1) IEC-320-C14



Cable Length (m)	3
Voltage	230V
Current	10
Current Monitoring	Yes
Phase	Single-phase
Frequency	50Hz

### Output

Grip cable retention	Yes
----------------------	-----

Outlets



Outlet Control	No
----------------	----

### Protection & Filtering

Spike/Surge Suppression	None
-------------------------	------

EMI/RFI Filter	None
----------------	------

### Control & Interface

Daisy Chain	8 ePDUs
-------------	---------

Operating Temperature	60 Degrees C
-----------------------	--------------

Hot Swap Network and Control	Yes
------------------------------	-----

Communication and Protocols	HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
-----------------------------	--

Optional Temperature and Humidity probe	EMP001
---	--------

Environmental Interface	Yes
-------------------------	-----

Serial Interface	Yes
------------------	-----

Ethernet Interface	Yes
--------------------	-----

Voltage Monitoring	Yes
--------------------	-----

### Metering and Switching

Metering	Outlet and Equipment Monitoring across A and B feed
----------	---

Metering Characteristics	V, W, A and kWhr, Active power, Apparent Power, Peak Power
--------------------------	--

Metering Accuracy	IEC Class 1 Billing grade Accuracy
-------------------	------------------------------------

Level 3 PUE measurements	Yes
--------------------------	-----

Circuit breaker status monitoring	Yes
-----------------------------------	-----

Switching	Outlet and Equipment Switching across A and B feed
-----------	--

### Environmental & Approval Standards

Approvals	CB, CE, EN 60950-1:2006/A11:2009/A1:2010/A12:2011 Safety - Part 1: General Requirements, IEC 60950-1(ed.2), IEC 60950-1(ed.2);am1 EN 55022:2010 Radio Disturbance characteristics - Limits and methods of measurement. EN 55024:2010 Immunity characteristics - Limits and methods of measurement.
-----------	--

Electromagnetic compatibility	EN 61000-6-2:2005 Part 6-2: Generic standards - Immunity for industrial environments EN 61000-6-4:2007+A1:2011 Part 6-4: Generic standards - Emission standard for industrial environments
-------------------------------	--

Environmental	RoHS Directive – 2011/65/EU, EN 50581 : 2012, REACH Regulation (CE No. 1907/2006), WEEE directive 2012/19/EU, PEP ecopassport (Basic ePDUs) Packaging: 100% recycled, 100% recyclable: no
---------------	---

plastic, no metal, no foam.

Manufacturing Plant

ISO 9001:2008 / ISO 14001:2004

## Warranty

Standard warranty

2 years

[Privacy Policy](#)  
[Terms & Conditions](#)  
[Copyright](#)

© 2022 Eaton  
All Rights Reserved