EMIB04

General	
Style Number	EMIB04
Part Number	EMIB04
Availability	Usually in stock
U Height	24 [Minimum U rack]
MIB	available for download

Physical	
Dimensions (H x W x D, mm)	52x53x1070
Mounting Style	Button mounting on rear and sides, variable mounting bracket
Form factor	0U

Input	
Max kW	4
Plug	(1) IEC 60309 16A
Cable Length (m)	3
Voltage	230V
Current	16
Current Monitoring	Yes
Phase	Single-phase
Frequency	50Hz

Output	
Grip cable retention	Yes
Outlets	

	(20) IEC-320-C13 (4) IEC-320-C19
Outlet Control	No

Protection &Filtering	
Spike/Surge Suppression	None
EMI/RFI Filter	None

Control &Interface	
Daisy Chain	8 ePDUs
Operating Temperature	60 Degrees C
Hot Swap Network and Control	Yes
Communication and Protocols	HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
Optional Temperature and Humidity probe	EMPDT1H1C2
Serial Interface	Yes
Environmental Interface	Yes
Ethernet Interface	Yes
Voltage Monitoring	Yes

Metering and Switching	
Metering	Input, Branch, Phase
Metering Characteristics	V, W, A and kWhr, Active power, Apparent Power, Peak Power
Metering Accuracy	IEC Class 1 Billing grade Accuracy

Environmental &Approval Standards	
Approvals	CB, CE, EN 60950-1:2006/A11:2009/A1:2010/A12:2011 Safety - Part 1: General Requirements, IEC 60950-1(ed.2), IEC 60950-1(ed.2);am1 EN 55022:2010 Radio Disturbance characteristics - Limits and methods of measurement. EN 55024:2010 Immunity characteristics - Limits and methods of measurement.
Electromagnetic compatibility	EN 61000-6-2:2005 Part 6-2: Generic standards - Immunity for industrial environments EN 61000-6-4:2007+A1:2011 Part 6-4: Generic standards - Emission standard for industrial environments
Environmental	RoHS Directive – 2011/65/EU, EN 50581 : 2012, REACH Regulation (CE No. 1907/2006), WEEE directive 2012/19/EU, PEP ecopassport (Basic ePDUs) Packaging: 100% recycled, 100% recyclable: no plastic, no metal, no foam.
Manufacturing Plant	ISO 9001:2008 / ISO 14001:2004

Warranty	
Standard warranty	2 years

Privacy Policy
Terms & Conditions
Copyright

© 2022 Eaton
All Rights Reserved